

Multi-Wash: A concentrated biodegradable cleaner used to clean painted and stained surfaces such as decks, fences, logs and siding. Dilute Multi-Wash to the prescribed strength for use on vinyl, fiberglass, concrete and masonry surfaces. Sansin Multi-Wash removes dirt, mold, mildew, water damage and iron stains.

FEATURES

- For interior and exterior surfaces
- Biodegradable
- Non flammable
- Zero VOC

IMPORTANT

Product Data Sheets are based on "ideal" work conditions. Due to wood variability and varying environmental conditions, it is strongly recommended that the end-user needs to determine that the application conditions, coating product system, and techniques are suitable to reach the desired results. Please see Conditions of Sale.

APPLICATIONS

Recommended for use on new and old wood surfaces such as decks, fences, siding, logs, board and batten and timbers. It can also be used on vinyl, fiberglass, concrete and masonry surfaces.

CHARACTERISTICS

- Coloring Turquoise/Blue
- Odor Low
- Form Liquid
- Specific Gravity (g/cm3) 1.00-1.05
- Density (lbs/gal) 8.30- 8.40
- pH 1.8- 2.3
- Viscosity, @Zahn 2 @21°C 17.5 sec +/- 1 sec
- Solvents N/A
- Freezing Point 0°C
- Diluent Water
- Cleanup Soap & Water
- Drying Time (To touch) @ 20°C (68°F)..... Do not allow to dry
- Coverage (Depending on coating appearance and thickness) 100-200 sq.ft./US gal.
- Shelf life Loses strength slowly over time
- Solids < 1%
- VOC (g/l) 0 g/l

PACKAGING

Available in 1 gallon US plastic containers.

PREPARATION

- Substrate must be dry.
- Temperature above 10°C (50°F).
- Spray vegetation with water or shield off before and during application.

- Protect bordering areas with drop sheets and/or tape off with poly.
- Do not allow this product to contact metal, fabric, floor coverings or outdoor furniture.
- Keep children and pets away from work area while using Multi-Wash.

APPLICATION METHODS

- Dilute with water up to 12:1 (12 parts water: 1 part Multi-Wash).
- 2:1 dilution for tough stains and heavy soiling.
- 5:1 dilution when preparing wood stains, painted surfaces or fiberglass.
- 12:1 dilution for vinyl, siding materials, masonry and stucco surfaces.
- Apply a liberal and uniform application using brush, roller or spray.
- On vertical surfaces start at the bottom and work your way up.

WORKING PROCEDURE

- Do not allow to dry as this will require reapplication.
- Do not apply in direct sunlight.
- Allow the product to dissolve coating for at least 15 minutes.
- Thoroughly rinse the surface using a garden hose or low pressure power washer (max pressure - 500psi).
- Direct the power washer wand with the grain of the wood.
- Do not stop the wand on the wood as this may mark the wood surface.
- Allow the wood to dry completely.

STORAGE

- Close container tightly.
- Store in a cool dry place.
- Avoid exposure to sunlight.
- Do not reuse container.
- Do not allow freezing.
- Rinse container thoroughly before disposal.

Distributed By:

Schroeder Log Home Supply, Inc.
1-800-359-6614 www.loghelp.com

Multi-Wash

ENVIRO STAIN®



EASY TO USE 

NON FLAMMABLE

CAN BE USED ON VARIOUS SURFACES

ECO FRIENDLY 



Multi-Wash



SAFETY

See Material Safety Data Sheet.

WARNING TO USERS

Keep out of reach of children, if swallowed immediately drink two glasses of milk or warm water. Do not induce vomiting. Call physician immediately. Avoid contact with skin or eyes; flush with soap and water. Avoid breathing of vapor or mist. Wear properly fitted NIOSH approved respirator. The information contained in this document is given in good faith based on our current knowledge. The use of the product is beyond the control of The Sansin Corporation, and no guarantees, expressed or implied, are made as to the result to be obtained if not used in accordance with the published Directions for Use. The Sansin Corporation does not assume any legal responsibility for use or reliance on same. This information must on no account be used as a substitute for necessary field tests, which alone can ensure that the product is suitable for the expected use. Before using any product, read its label.

CONDITIONS OF SALE

The only obligation of the manufacturer and seller shall be to replace such quantity of Sansin product that is proven to be defective. Proof of purchase is required. Seller or manufacturer shall not be liable for any loss or damage connected with the use and/or handling of this product. All labor costs are specifically excluded. User should determine suitability of product for the intended use before application. User assumes all risk and liability in connection therewith. This warranty is expressly made in lieu of any and all other rights, warranties, conditions and remedies, express or implied, including but not limited to any implied warranty or condition of merchantability, fitness for a particular purpose, and any warranty or condition arising out of a course of dealing, a custom or usage of trade. If any distributor or seller of product offers warranties or remedies which differ from those offered by Sansin, Sansin accepts no responsibilities for such warranties or remedies.

© ALL RIGHTS RESERVED
JUNE 2019

